

# PrepAwayExam

PrepAwayExam

> Contact Us

Login / Register

Search...



HOME

ALL VENDORS

★ GUARANTEE

? FAQ

TESTIMONIALS

CART (0)

## Pass Your Next Certification Exam Fast!

Everything you need to prepare, learn & pass your certification exam easily.

365 days free updates. First attempt guaranteed success.

Try **Online Engine** before you buy

### Instant Download



After Payment, our system will send you the products you purchase in mailbox in a minute after payment. If not received within 2 hours, please contact us.

### 365 Days Free Updates



Free update is available within 365 days after your purchase. After 365 days, you will get 50% discounts for updating.



### Money Back Guarantee

Full refund if you fail the corresponding exam in 60 days after purchasing. And Free get any another product.



### Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.

<http://www.prepawayexam.com/>

High-efficient Exam Materials are the best high pass-rate Exam Dumps

**Exam** : **JN0-696**

**Title** : Security Support,  
Professional (JNCSP-SEC)

**Vendor** : Juniper

**Version** : DEMO

NO.1 You are having problems establishing an IPsec tunnel between two SRX Series devices.

What are two explanations for this problem? (Choose two.)

- A. proposal mismatch
- B. antivirus configuration
- C. preshared key mismatch
- D. TCP MSS clamping is disabled

**Answer:** B,D

NO.2 Two SRX Series devices are having problems establishing an IPsec VPN session. One of the devices has a firewall filter applied to its gateway interface that rejects UDP traffic.

What would resolve the problem?

- A. Disable the IKE Phase 1 part of the session establishment.
- B. Disable the IKE Phase 2 part of the session establishment.
- C. Change the configuration so that session establishment uses TCP.
- D. Edit the firewall filter to allow UDP port 500.

**Answer:** A

NO.3 Your SRX Series device has the following configuration:

```
user@host> show security policies
```

```
...
```

```
Policy: my-policy, State: enabled, Index: 5, Sequence number: 1
```

```
Source addresses: any Destination addresses: any
```

```
Applications: snmp
```

```
Action: reject
```

```
From zone: trust, To zone: untrust
```

```
...
```

When traffic matches my-policy, you want the device to silently drop the traffic; however, you notice that the device is replying with ICMP unreachable messages instead.

What is causing this behavior?

- A. the snmp application
- B. the reject action
- C. the trust zone
- D. the untrust zone

**Answer:** C

NO.4 You want to allow remote users using PCs running Windows 7 to access the network using an IPsec VPN. You implement a route-based hub-and-spoke VPN; however, users report that they are not able to access the network.

What is causing this problem?

- A. The remote clients do not have proper licensing.
- B. Hub-and-spoke VPNs cannot be route-based; they must be policy-based.
- C. The remote clients' OS is not supported.
- D. Hub-and-spoke VPNs do not support remote client access; a dynamic VPN must be implemented instead.

**Answer: B**

NO.5 You notice that the secondary node of a chassis cluster has become disabled.

What caused this behavior?

- A. The fxp0 interface on the secondary device failed.
- B. The control link between the devices failed.
- C. A reth on the secondary device failed.
- D. An IPsec tunnel between the two devices failed.

**Answer: D**

NO.6 Users at a branch office report that they cannot reach an internal Web server. The users connect through a single SRX Series device to reach the Web server. A security policy has been configured on the device that allows traffic to flow between interfaces in the Trust zone.

What is causing this problem?

- A. The interface on the device that connects to the Web server is not in the Trust zone.
- B. The IPsec VPN connection between the users and the Web server is down.
- C. There is a host inbound traffic configuration problem.
- D. There is an antispam configuration problem.

**Answer: C**